





Ref No. SI/LP/25-12 - w.e.f 25th March, 2025


RATE IN RS.			
NATIONAL CABLES - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC GRADE BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UP TO 1100 V CONFORMING TO IS 694:2010.			
CONDUCTOR (AREA SQ.MM)	RATE PER 90 M COIL	STANDARD PACKING FOR 90 METER	RATE PER 180M COIL
0.5	742	20	1,410
0.75	1,078	20	2,048
1.0	1,412	20	2,683
1.5	2,072	20	3,937
2.5	3,433	8	6,523
4	5,041	8	9,578
6	7,527	8	14,301


RATE IN RS.			
NATIONAL CABLES - FRLSH PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES WITH BRIGHT ANNEALED ELECTROLYTIC GRADE BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UP TO 1100 V CONFORMING TO IS 694:2010.			
CONDUCTOR (AREA SQ.MM)	RATE PER 90 M COIL	STANDARD PACKING FOR 90 METER	RATE PER 180M COIL
0.5	761	20	1,446
0.75	1,100	20	2,090
1.0	1,437	20	2,730
1.5	2,101	20	3,992
2.5	3,477	8	6,606
4	5,102	8	9,694
6	7,611	8	14,461

National Cables FR & FRLSH are available in seven common colours : Red, Yellow, Blue, Black, Green, Grey, White

RATE IN RS. PER 100 METERS		
NATIONAL CABLES - FLEXIBLE - FR AND FRLSH PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC GRADE BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UP TO 1100 V CONFIRMING TO IS 694:2010		
CONDUCTOR (AREA SQ.MM)	SINGLE CORE FR	SINGLE CORE FRLSH
10	14,610	14,763
16	23,003	23,189
25	35,768	36,055
35	50,187	50,555
50	71,875	72,379
70	104,134	104,841
95	137,116	137,995
120	175,301	176,386
150	217,573	219,167
185	268,460	270,449
240	353,743	356,249

RATE IN RS. PER 100 METERS														
NATIONAL CABLES - MULTICORE FLEXIBLE - FR PVC INSULATED & PVC ROUND SHEATHED MULTICORE BRIGHT ANNEALED BARE COPPER CONDUCTOR FLEXIBLE CABLES FOR VOLTAGE GRADE UP TO 1100 V AS PER IS 694:2010														
SQ.MM	TWIN TWISTED	2 CORE	3 CORE	4 CORE	5 CORE*	6 CORE*	7 CORE*	8 CORE*	10 CORE*	12 CORE*	14 CORE*	16 CORE*	19 CORE*	24 CORE*
0.5	1,898	2,051	2,868	3,671	4,473	5,341	6,014	7,009	8,797	10,282	11,854	13,475	15,794	20,275
0.75	2,719	2,818	3,954	5,128	6,323	7,562	8,572	9,961	12,502	14,686	16,972	19,318	22,703	29,074
1.0	3,592	3,591	5,058	6,590	8,150	9,756	11,103	12,878	16,162	19,041	22,037	25,101	29,545	37,780
1.5	5,183	5,059	7,186	9,403	11,777	14,107	16,123	18,659	23,408	27,665	32,064	36,545	43,084	54,990
2.5	8,605	8,265	11,574	15,205	19,065	22,859	26,220	30,300	38,017	45,053	52,286	59,633	70,401	89,761
4	13,283	12,779	18,413	24,219										
6			27,030	35,625										
10			45,272	59,764										
16 *			70,086	92,668										
25 *			108,501	143,546										
35 *			169,723	226,285										
50 *			241,867	322,488										
70 *			337,617	450,155										
The items marked * are non stock items. Please refer to marketing department for delivery confirmation indicating quantity, packing length, colour etc. Packing: Cables shall be supplied in Standard length of 100 M														

RATE IN RS. PER 100 METERS	
NATIONAL CABLES - SUBMERSIBLE - THREE CORE FLAT CABLES WITH BARE COPPER CONDUCTOR INSULATED AND SHEATHED WITH PVC FOR SUBMERSIBLE PUMP MOTORS WITH VOLTAGE GRADE UP TO 1100 VOLTS CONFORMING TO AND MARKED WITH IS 694:2010	
CONDUCTOR (AREA SQ.MM)	Rate
1.5	7,951
2.5	12,451
4	19,280
6	27,569
10	48,525
16	74,983
25	118,696

RATE IN RS. PER 100 METERS	
NATIONAL CABLES - TELEPHONE CABLES WITH HIGH DENSITY PVC INSULATED, SOLID ANNEALED HIGH CONDUCTIVITY TINNED COPPER WITH DIA 0.5MM, PAIRED, POLYESTER TAPED AND SHEATHED WITH HIGH OXYGEN INDEX FIRE RETARDANT PVC COMPOUND, GENERALLY CONFORMING TO ITD SPECIFICATIONS G/WIR-06/02 MAY 94	
CONDUCTOR (AREA 0.50 MM)	
1 Pair	881
2 Pair	1,683
3 Pair	2,431
4 Pair	3,183
5 Pair	3,922
10 Pair	7,377

A nylon ripcord is provided for slitting the jacket without damaging the insulated cores. The outer sheath colour is Grey.

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy
- National Cables are printed with Brand logo (NC), Brand Name (National Cables), Size (Sq.mm), Voltage Grade and ISI Logo.
- Orders placed are subject to Company's confirmation.
- Goods are dispatched by us on purchaser's risk.
- This price list supersedes our earlier price list.
- Disputes, if any, are subject to Uttar Pradesh Jurisdiction.
- Prices are subject to change without notice. Company reserve the right to issue amendments, which may arise due to any errors in the list price.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS : 8130: 1994 with its related classes and tables.

* Each cores of the wire is in different colour for identification.

SUNRAY INDUSTRIES

Regd Office : K-51, Connaught Circus, New Delhi - 110001.

T : +91 - 11 -2341 2618 / 6459 / 6458

M : +91 - 9910691538

E: sales@nationalcables.in

www.nationalcables.in